

<b>MAGNIFICATION</b>		<b>SLIT</b>	
Type	Galilean	Slit width	Continuous from 0 to 14mm
Cylinder	12.5x	Slit length	Continuous from 1 to 14mm
Selection	Drum rotation	Aperture	Diam.: 0.2, 1, 2, 3, 5, 10, 14mm
		Slit angle	0 to 180°
		Tilt	5, 10, 15, 20°
		<b>ILLUMINATION LAMP</b>	
Field of view :	10x (22mm) - 16x (13.5mm)		6V, 20W halogen lamp
	25x (8.5mm)	<b>FILTERS</b>	
			25 Watt
			Heat-absorbing, ND, Red-free, Cobalt blue
<b>BASE</b>		<b>POWER-SUPPLY</b>	
Longitudinal movement	90 mm	CE Conformity marking	220/110V (±10%)
Lateral movement	100 mm	<b>DIMENSIONS AND WEIGHTS</b>	
Vertical movement	30 mm	450 (W) x 500 (D) x 740 (H) mm	
Chinrest (vertical)	80 mm	24kg	
		<b>OPTIONS</b>	
		Yellow filter, Background illumination, Applanation tonometer, Polarized filter, Observation tube, H'ruby lens	

As improvements are made, these specifications and pictures are not contractually binding and may be changed without prior notice.