



FEMTIS® Comfort toric FB-313 MF15T0-T3

One-piece toric posterior chamber lens for extended depth of focus and high contrast sensitivity with aspherical surface for fixation in the automated continuous circular capsulotomy

	standard-toric
Product	FEMTIS® Comfort took FB-313 MF15T0-T3 Auto-CCC EDOF aspheric
	Auto-ccc
Туре	Foldable one-piece toric EDOF-IOL for capsular bag and additional capsulotomy fixation
Optic Size	5.7 mm
Overall Length	10.5 mm
Haptic Angulation	0°
Optic Design	Biconvex Sector-shaped near vision segment - anterior: +1.5D Aspherical and toric surface -posterior Spherical aberration neutral
IOL Design	Plate haptic with additional Clip-haptics Optic and haptic with square edges
Material	HydroSmart® - a copolymer, consisting of hydrophilic acrylates with hydrophobic surface UV absorbing
Available Diopters	SE +15.0D to +30.0D (0.5D) cyl.: T0 +0.75D T1 +1.5D T2 +2.25D T3 +3.0D
Refractive Index	1.46
A-Constant (nominal)	117.8
Sterilisation	Steam sterilisation
Storage	Supplied at sterile water
Recommended Injector-Sets	Check compatibility of IOL with injector matrix provided at www.lentis-eifu.com

Revision: QF2261v3