



LENTIS® Comfort^{toric}
LS-313 MF15T0-T6

One-piece toric posterior chamber lens for extended depth of focus and high contrast sensitivity with aspherical surface

Product	LENTIS® Comfort^{toric} LS-313 MF15T0-T6 standard-toric EDOF aspheric
Type	Foldable one-piece toric EDOF-IOL for capsular bag fixation
Optic Size	6.0 mm
Overall Length	11.0 mm
Haptic Angulation	0°
Optic Design	Biconvex Sector-shaped nearvision segment - anterior: +1.5D Aspherical and toric surface -posterior Spherical aberration neutral
IOL Design	Plate haptic Optic and haptics with square edges
Material	HydroSmart® - a copolymer, consisting of hydrophilic acrylates with hydrophobic surface UV absorbing
Available Diopters	SE: +10.0D to +30.0D (0.5D) cyl.: T0 +0.75D T1 +1.5D T2 +2.25D T3 +3.0D T4 +3.75D T5 +4.5D T6 +5.25D
Refractive Index	1.46
A-Constant (nominal)	118.0
Sterilisation	Steam sterilisation
Storage	Supplied at sterile water
Recommended Incision Size	≥ 2.2 mm
Recommended Injector-Sets	Check compatibility of IOL with injector matrix provided at www.lentis-eifu.com

Revision: QF2246v1