



15

LENTIS® Comfort LS-313 MF15

One-piece posterior chamber lens for extended depth of focus and high contrast sensitivity with aspherical surface

Product

LENTIS® Comfort **LS-313 MF15**

EDOF

aspheric

Type	Foldable one-piece EDOF-IOL for capsular bag fixation
Optic Size	6.0 mm
Overall Length	11.0 mm
Haptic Angulation	0°
Optic Design	– Dioptres: Convex-concave + Dioptres: Biconvex Sector-shaped nearvision segment - anterior: +1.5D Aspherical surface - posterior Spherical aberration neutral
IOL Design	Plate haptic Optic and haptics with square edges, posterior 360° continuous barrier effect
Material	HydroSmart® - a copolymer, consisting of hydrophilic acrylates with hydrophobic surface UV absorbing
Available Diopters	SE –10.0D to –1.0D (1.0D) SE ±0.0D to +36.0D (0.5D)
Refractive Index	1.46
A-Constant (nominal)	118.0
Sterilisation	Steam sterilisation
Storage	Supplied at sterile water
Recommended Incision Size	≥ 1.8 mm
Recommended Injector-Sets	Check compatibility of IOL with injector matrix provided at www.lentis-eifu.com

Revision: QF2239v1